

DM40IP12V30 4MP IP Network Dome Camera

Key features Specifications

- 1/3" 4MP CMOS Sensor
- 2560 x 1440 resolution @20FPS
- POE (802.3af) or 12VDC
- WDR, 3D DNR
- 2.8-12mm Varifocal lens
- IP 66 Weatherproof
- Up to 30m IR night vision
- Support Cloud storage, P2P



Model Number	DM40IP12V30
Style	IR Vandal Proof Dome
Image Sensor	1/3" 4MP CMOS
Type	3516D+OV4689
Resolution	2560 x 1440 @20FPS, 2304x1296@30FPS
Shutter	1/25—1/10000s(adjustable)
WDR	Support
Digital noise	3D DNR
Day/Night	ICR-infrared filter
Video Compression	H.264/H.265/AVI/JPEG
Bit Rate	64-12000Kbps
Image setting	Brightness, contrast, saturation, sharpness
Backlight Compensation	Support
Storage function	FTP / Local / NVR / SMTP / Cloud storage
Interface protocol	Onvif 2.4
Alarm Functions	Motion detection / Privacy
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
General functions	Tri-stream / Mirror / Corridor / ROI
Communication interface	RJ45(10M/100M/1000M)Adaptive Ethernet port
Vandal Resistant	Yes
Dimensions (mm)	121(Ø)x93(H)
Weight (g)	800
Environment	-20°C ~60°C, 0%-90%RH No Condensation
Weatherproof	IP66
Power	DC12V±5% / PoE(802.3af)